VIMCOM AG

Dorfstrasse 55 CH-8103 Unterengstringen



MODEL 173581/K-5	SPECIFICATIONS	
ANTENNA TYPE	Dual band flexible full ½ λ mobile antenna for onglass mounting	
FREQUENCY	890-960 + 1710-1880 MHz (GSM DUAL)	
IMPEDANCE	Nom. 50 Ohm	
POLARISATION	Vertical	
GAIN	Low band: 0 dBd (2,15 dBi) High band: 0 dBd (2,15 dBi)	
BANDWIDTH	See 'FREQUENCY'	
VSWR	< 1.5 at frequency resonance	
MAX. POWER	Low band : 25 Watt High band: 10 Watt	
COLOUR	Black	
DIMENSIONS	60 x 38 x 16 mm (internal box) 60 x 38 x 21 mm (external mount) (whip length approx. 80 mm)	
WEIGHT	Approx. 250 g (cable included)	
MOUNTING PLACE	On front or rear window screen	
MOUNTING ANGLE	Base is 45 ° tiltable in all directions	
MATERIAL	ABS, PE, PC-board, 3M adhesives and brass	



THREAD	M5
CABLE	5m RG 58 FME/FME cable included (110500)

SPARE PARTS	WHIP	Art. No. 1735
	RE-INSTALATION KIT	Art. No. K-80
	REPLACEMENT MOUNT	Art. No. A-81