

| MODEL | SPECIFICATIONS |
|----------------|---|
| ANTENNA TYPE | Rigid mobile antenna for on-glass mounting |
| FREQUENCY | 872-960 MHz |
| IMPEDANCE | Nom. 50 Ohm |
| POLARISATION | Vertical |
| GAIN | 0 dBd (2,15 dBi) / 3 dBd (5.15 dBi) |
| BANDWIDTH | See 'FREQUENCY' |
| VSWR | < 1.5 at frequency resonance |
| MAX. POWER | 25 Watt |
| COLOUR | Black |
| DIMENSIONS | 61 x 39 x 19 mm (internal box) 62 x 40 x 43 mm (external mount) (whip length approx. 70 / 295 mm) |
| WEIGHT | Approx. 120 / 150 g |
| MOUNTING PLACE | On window screen |
| MOUNTING ANGLE | Base is 180 ° tiltable |
| MATERIAL | ABS, PE, PC-board, 3M adhesives, brass and stainless steel |

| | |
|--------|------------------------|
| THREAD | M5 |
| CABLE | FME cable not included |

| | | | | |
|------|---------------|---------------|---------------|-------------|
| WHIP | 872 - 960 MHz | 0 dBd / 55mm | Art. No. 3497 | Base No. 77 |
| | 872 - 960 MHz | 3 dBd / 275mm | Art. No. 3493 | Base No. 77 |

| | | |
|-------------|--------------------|---------------|
| SPARE PARTS | RE-INSTALATION KIT | Art. No. K-80 |
|-------------|--------------------|---------------|

